

## DSMH 23.6 WGF | 23.6" Active Matrix With Glass Front High Resolution

### DSMH 23.6 WGF

LCD Panel Type	23.6" Active Matrix With Glass Front High Resolution
Maximum Resolution	1920 (H) x 1080 (V)
Active Display Area	521.28 (H) x 293.22 (V) mm
Pixel Pitch	0.2715 (H) x 0.2715 (V)
Bezel Thickness	27mm
Contrast Ratio	1000 : 1 Ratio
Brightness	300 cd/m <sup>2</sup>
Response Time	3.5ms
Viewing Angle	80 / 80/ 85 / 85
Display Colours	16.7 M
Video Synchronization	TTL Positive or Negative
PC Compatible Frequency	30-80KHz(H) / 50-75Hz(V) Max. 1920 x 1080
Adjustable Colour Temperature	Yes
Video Compatibility	Multi-Standard for NTSC / PAL
Aspect Ratio	16 : 9 Ratio
VGA Auto Frequency Correction	Yes
Number of Speakers	Right x 1 Left x 1
Sound Demodulation	Stereo. Audio
Mute	Yes
Work Humidity	20 % - 70 %
Work Temperature	- 10 to 50 °C
Volume +/- Power ON/OFF	Yes



### IN/OUT INTERFACE

Video Interface	<ul style="list-style-type: none"> <li>• DC VGA x 1, Video in x 2 (BNC)</li> <li>• Video Out x 2 (BNC)</li> <li>• S-Video x 1 HDMI input x 1</li> </ul>
Audio Interface	Audio in x 1
Power Interface	AC in x 1
Termination	75 Ohms (Automatic termination)
Safety & EMC Certification	CE / FCC / ROHS / Energy Star
Vesa Standard Mount	100 x 100mm
Stand Type	Vesa Mount
Colour	Black
LCD Dimension (Without Base)	615 (W) x 305 (H) x 81 (D) mm
Packing Dimension	640 (W) x 500 (H) x 165 (D) mm
NET Weight	13.2 Kgs
GROSS Weight	14.4 Kgs

### OSD CONTROLS

Contrast, Brightness, Clock, Phase, H-Position, V-Position, Language, Reset

### OSD LANGUAGE

English, French, German, Spanish, Italian, Chinese

### ACCESSORIES

Power Supply / Kettle Lead / VGA Cable / Audio Cable / User Manual, Remote

### POWER

Power Supply	Internal
Voltage	AC100 - 240V 50 / 60Hz
Power Consumption	< 60W