

AS19TFT

19" Professional CCTV LCD MONITOR



I/O Interface

RCA x 2, VGA x 1, PC Audio x 1, HDMI x 1
BNC Input x 2, BNC Output x 2

MODEL	AS19TFT
Diagonal size	19"
Viewable size	376.3mm(H) x 301.06mm (V)
Display resolution	1280(H) x 1024(V)mm
Pixel pitch	0.294(H) x 0.294(V)mm
Contrast ratio	800:1
Brightness	300cd/m2
Response time Tr./Tf.	5ms
Resolution	SXGA
System	PAL / NTSC
Viewing angle	Vertical - 80°~ 80° Horizontal - 80° ~ 80°
Display mode	Video 1 / Video 2 / PC / HDMI
Operating temperature	5°~ 40°C, Storage: -25°~60°
Composite input	BNC x 2, RCA x 2, VGA x 1, PC Audio x 1, HDMI x 1
Composite output	BNC x 2
Voltage input	100~240V, 50/60Hz
Power consumption	240W
Standby power consumption	3.4W
AC power	AC 100~240V 50/60Hz
Dimensions	425 x 430 x 195
Net weight	6 Kgs
Safety	FCC-DOC, UL/CUL, CE, ROHS

specification subject to change without notice