

AS42TFT

42" LCD BNC MONITOR

Key Features

- Pro 3D De-interlace
- 3D comb filter High quality motion adaptive
- 3D comb filter High quality motion adaptive
- 4H comb filter adaptive for the best image quality
- 3D noise reduction
- 2 BNC INPUT , 2 BNC OUTPUT, 1 VGA, 2 RCA, 1 PC Audio, 1 HDMI
- Looping Function

Optional Accessory

Wall Mount Bracket: WM-32

Input/Output Panel



MODEL	AS42TFT
Diagonal size	42"
Resolution	WXGA
System	PAL / NTSC
Active area (mm)	930.25(H) x 523.01(V)
Aspect ratio	16:9
Display resolution	1366 x 768
Definition	Support 1080P
Brightness	500 cd/m2
Contrast ratio	1000:1
Number of colours	16.7M
Response time (tr/TF)	8 ms
Composite Input	BNC x 2, VGA x 1, RCA x 2, PC Audio x 1, HDMI x 1
Composite Output	BNC x 2
Voltage input	100~240V, 50/60Hz
Power consumption	240W
Standby power Consumption	3.4W
OSD control	Picture Mode, Contrast, Brightness, Colour, Tint, Sharpness, Colour Temp, DNR
OSD languages	English, Germany, French, Italian, Spanish, Russian, Turkish, Japanese, Polish
Auto adjustment	Yes
De-interlace	Yes
Wall mount	Yes
Accessories	Power cord, Manual, Adapter, VGA cable, HDMI Cable
Tilt	-5°~15°C
Safety	UL/CUL, FCC-DOC, CE, ROHS

specification subject to change without notice