

DS19TFT

19" LCD BNC MONITOR

Key Features

- The best display for CCTV cameras, DVR, multiplexer and other surveillance equipments.
- POS / ATM terminals.
- 3D comb filter High quality motion adaptive
- 4H comb filter adaptive for the best image quality
- 3D noise reduction
- 1 BNC INPUT , 1 BNC OUTPUT ; LOOPING FUNCTION



MODEL	DS19TFT
Display Type	19"(4:3) Active Matrix TFT LCD Module
Resolution	1280(H) x 1024(V) SXGA
Pixel Pitch	0.294(H) x 0.294(V) mm
Contrast ratio	500:1 (TYP.)
Brightness	300 Cd/m2
Response time	8ms
Colours	16.7M
Display area	376.32mm(H) x 301.056mm(V)
Viewing Angle L/R	80°/80°
Viewing Angle U/D	75°/75°
OSD Control	Contrast, Brightness, Clock, Phase, H-Position, V-Position, Language.
Composite Inputs	(VGA)x1,(S-Video)x1, (PC Audio)x1,(BNC)x1
Composite Outputs	(BNC)1x
Speaker	2.5W x 2 Multimedia Speakers
Power consumption	40W in "ON" mode
Wall hanging	Yes
Auto adjustment	Yes
OSD Language	English, Germany, French, Italian, Spanish
Accessories	Power cord, Adapter, User's guide, Audio cable
Dimensions	430(W) x 414(H) x 30(D) mm
Weight	N.W.: 5.8kgs, G.W.: 7.5kgs
Certificate	Energy Star, FCC-DOC, CE, ROHS

specification subject to change without notice