

DSH19TFT2

19" LCD MONITOR
HDMI, PIP, POP

Key Features

- The best display for CCTV cameras, DVR, multiplexer and other surveillance equipments.
- POS / ATM terminals.
- 3D comb filter High quality motion adaptive
- 4H comb filter adaptive for the best image quality
- 3D noise reduction
- 2 BNC INPUT, 2 BNC OUTPUT;
LOOPING FUNCTION
- Support POP and PIP



MODEL	DSH19TFT2
Display Type	19"(4:3) Active Matrix TFT LCD Module
Resolution	1280(H) x 1024(V) SXGA
Pixel Pitch	0.294(H) x 0.294(V) mm
Display Area	376.32mm(H) x 301.056mm(V)
Contrast ratio	500:1 (TYP.)
Brightness	300 Cd/m2
Response time	8ms
Colours	16.7M
Viewing Angle L/R	80°/80°
Viewing Angle U/D	75°/75°
OSD Control	Contrast, Brightness, Clock, Phase, H-Position, V-Position, Language.
Composite Inputs	(VGA)x1, (S-Video)x1, (PC Audio)x1, (BNC)x2, HDMI
Composite Outputs	(BNC) x 2
Speaker	2.5W x 2 Multimedia Speakers
Power consumption	40W in "ON" mode
Wall hanging	Yes
Auto adjustment	Yes
OSD Language	English, Germany, French, Italian, Spanish
Dimensions	430(W) x 414(H) x 30(D) mm
Accessories	Power cord, Adapter, User's guide, Audio cable
Weight	N.W.: 5.8kgs, G.W.: 7.5kgs
Certificate	Energy Star, FCC-DOC, CE, ROHS

specification subject to change without notice