

PVM32

32" LCD Public Viewing Monitor
with WDR Camera

Key Features

- . 32" LCD Public viewing monitor
- . 3 in 1: LCD/ Cameras/Media player
- . Built in media player for advertisement or information publish
- . Suitable for security & advertisement application , & for Department Store, Supermarket. Entrance of chain store. video rental shop, restaurant, hotel etc.
- . 31.51 inch diagonal viewing size
- . Adaptive 3D comb filter for life like and sharp images
- . PIP and POP for multi-screen arrangement
- . Equipped with WDR cameras for clear viewing under strong backlight
- . 2nd cameras optional for different viewing angle and areas
- . Media Player built in for advertisement or public information
- . Sleek ID design
- . IR remote control



specification subject to change without notice

MODEL	PVM32	
LCD Spec.	LCD Display	31.51" TFT LCD
	Max. Resolution	1366(H) x 768(V)mm (WXGA)
	Lamp life time	60,000hrs
	Pixel Pitch	0.51075(H) x 0.51075(V)mm
	Contrast ratio(Typ.)	2500:1
	Brightness	Typ. 450 cd/m ²
	Response time	6.5 ms
	Viewing Angle	U:89°, D:89°, R:89°, L:89°
Camera-1	Effective Pixels	NTSC: 768(H) x 494(V) PAL: 752(H) x 582(V)
	Resolution	520TVL
	Min. Illuminatin	0.5Lux/F1.2 , 0.01lux(DSS)/F1.2
	Lens Type	3.3~12mm vari-focal lens
WDR Camera (option)	Effective Pixels	NTSC: 768(H) x 494(V) PAL: 752(H) x 582(V)
	Resolution	540TVL
	Min. Illuminatin	0.1Lux/F1.2
	Digital Zoom	ON (3X)/ OFF Selected on OSD menu
Media	Lens Type	DC Vari-Focal lens
	Media player	SD/MMC/ MS card reader
	USB	Upload content
	Format	Video/ Photo : Support JPEG,MJPEG/II/IV, MP3.
I/O connectivity	Video display format	Support JPEG, MJPEG/II/IV, MP3
	Audio	5W x 2
	IR remote controller	>= 8 meter @0 degree
	Video Input	S-Video in x1; YPbPr in x1,
Control	Video output	BNC output x2 (for camera out) ; S-Video output x1
	PC input	VGA inputx1; DVI inputx1
	Audio input	RCA x2 (L/R for YPbPr), RCA x 2 (mono for S-Video& BNC) Phone Jack X 1 (for VGA/DVI)
	Audio output	RCA jack x 2 (1 for Media output, 1 for S-Video& BNC)/Phonejack
Power	OSD Function	Camera. LCD. Media function
Environment	Power Input	Universal AC 90~264V, 50/60Hz
	Storage temp.	-20°C ~ 60°C
	Operation temp.	0°C ~ 40°C
	Operation humidity	20% ~ 85% (Non-Condensation)