

5.6" LCD Test Monitor

with Test Pattern Generator



Fully Featured:

- Light weight & compact size
- Resolution 320x234 pixels
- NTSC/PAL auto recognition
- Two video BNC input and one audio jack input
- Test pattern generator (colorbars/crosshatch/RGB/Dot)
- Multi-language support OSD
- Carrying strap and travel case
- Rechargeable battery and AC adaptor
- Anti-scratch & anti-reflectiveness visor
- Ideal for CCTV installation, on-site demonstration and testing
- Last memory for settings when powered off
- Power saving while no signal input




RS5.6TFT

5.6" LCD Test Monitor
with Test Pattern Generator


RS5.6TFT

5.6" LCD Test Monitor
with Test Pattern Generator

Test Pattern Generator




Side View



Description	
1	Power mode switcher (ON / OFF / Charge)
2	Power input jack (DC IN)
3	Audio input/ output
4	Video OUT
5	Video1 / Video 2 IN

Back View:



Description	
1	Rechargeable battery

Packing List

- . 5.6 TFT LCD Monitor x 1
- . Travel case with carrying & waist strap x 1
- . AC adaptor x 1
- . Rechargeable Li-poly battery x 1
- . 12VDC vehicle cigar lighter charger x 1
- . 3.5" stereo jack to RCA jack cable x 1
- . User Manual x 1

MODEL	RS5.6TFT	
LCD panel spec.	LCD display	Colour 5.6" LCD
	Screen size(Viewable size)	5.6"(113.3(H) x 84.7mm (V))
	Max.resolution	320(H) x 234(V)mm (4:3)
	Lamp lifetime	20,000 hrs
	Dot pitch	0.118(H) x 0.362(V)mm
	Contrast ratio	150:1Typ.
	Brightness	300cd/m ² (TYP.)
	Response time Tr/Tf	15/20ms (TYP.)
	Viewing angle L/R	45°/45°
	Viewing angle Up/Down	10°/30°
Front Control	Power on/off, Power/Recharge LED indicator, SOURCE, Up (Volume Increase) Picture (OSD menu), Down (Volume Decrease)	
Display mode	Video 1, Video 2, Test pattern	
OSD menu	Video	Language, Auto Off, Contrast, Brightness, Colour, Tint, Sharpness, Recall
Signal connector	Input	2 x BNC Inputs (1.0Vp-p75 Ω); 1 x Audio Input (3.5 Ω stereo Jack)
	Output	1 x BNC Outputs (2.0Vp-p75 Ω); 1 x Audio Output (3.5 Ω stereo Jack)
Audio speaker	1W (Max.)	
Environment considerations	Operating condition	Temperature: 0°C ~ 40°C
	Storage Condition	Temperature: -20°C ~ 60°C
Power Input	AC Input: 100 ~ 240V/1.5A, 50 / 60Hz	
Power Consumption	14W	
Power Supply	DC 9V	
Dimension	Net (WxHxD)	180x120x34mm
	Packing (WxHxD) (1pcs/Box)	256x175x116mm
	Weight	N.W.: 1.2kgs, G.W.: 1.6kgs
Stands/bracket supported	1/4" standard screw mount on bottom	
Rechargeable Battery Condition	Li-Poly battery (7.4V / 2650mAh)	
Safety	FCC, CE(EMC/LVD), UL, BSMI, CCC	
Material	FrontPanel	Plastic
	RearCover	Plastic
Optional accessories	Rechargeable battery	BT-088269

specification subject to change without notice