

### RSM8TFT

8" CCTV LCD MONITOR



Rear of Unit  
Hinge Stand as Photo Frame (option)



### Key Features

- . Durable metal housing
- . Rack mountable (side-by-side) for standard 19" rack
- . Resolution 800x600 pixels
- . NTSC/PAL auto recognition
- . 2 video BNC inputs
- . 4 RCA audio jacks for audio input/output
- . Multi-language OSD
- . Last memory for settings when powered off
- . Power saving while no signal input
- . Low power consumption with LED backlight
- . Key lock function

### Optional Accessories

**Rack Mount Bracket** : RK-80  
**Wall Mount Bracket** : DW-170  
**Wall Mount Stand** : RK212S

MODEL		RSM8TFT
LCD panel spec.	LCD display	Colour LCD 8" LCD Monitor
	Screen size(Viewable size)	8" (162 x122 mm, WxH)
	Max.resolution	800(H)x600 (V)mm
	Lamp lifetime	20,000 hrs
	Dot pitch	0.675(W)x0.2025 (H)mm
	Contrast ratio	500:1 Typ.
	Brightness	200 cd/m2 (TYP.)
	Response time Tr/Tf	10/15ms (TYP.)
	Viewing angle L/R	70° / 70°
	Viewing angle Up/Down	70° / 70°
Resolution		380TVL
Display mode		Video 1, Video 2, S-Video
OSD menu	Video	Language, Contrast, Brightness, Colour, Tint, Sharpness, Reset
Signal connector	Input	2 x BNC Inputs (1.0Vp-p 75Ω);
		1 x S-Video Input
	Output	1 x Audio Input (RCA Jack R,L)
		2 x BNC Outputs (2.0Vp-p 75Ω)
		1 x Audio Output (RCA Jack R,L)
Audio speaker		2W (Max.)
Environment considerations	Operating condition	Temperature: 0°C ~ 40°C
	Storage Condition	Temperature: -20°C ~ 60°C
Power Input		AC Input: 100 ~ 240V/1.5A, 50 / 60Hz
Power Consumption		18W
Power Supply		DC 12V
Dimension	Net (WxHxD)	190 x 173 x 25 mm
	Packing (WxHxD) (1pcs/Box)	280 x 244 x 97 mm
	Weight	N.W.: 1.1 kgs, G.W.: 1.5 kgs
Stands/bracket supported		Hinge Standard
Safety		FCC, CE (EMC/LVD), UL, BSMI, CCC
Optional accessories	Rackmount bracket	Option (Part number: RK-80) / (VESA Standard)
	Wallmount bracket	Option (75x75,100x100) (Part number: DW-170)
	Wallmounting stand	option (Part number RK-212S)

specification subject to change without notice