



# PUBLIC VIEW/DIGITAL SIGNAGE

## DS42PVM

LED back light with SD Card reader

### DS42PVM

Panel Type	42" (16:9) LED Public viewing Monitor Metal Cased
Maximum Resolution	1920(H) x 1080(V)
Active Display Area	930.24 ( H ) x 523.26 ( V ) mm
Pixel Pitch	0.1615 (H) x 0.4845 (V) mm
Contrast Ratio	6000 : 1
Brightness	450 cd/m <sup>2</sup>
Response Time	4.5 ms
Viewing Angle	U/D: 88° / 88°, L/R: 88° / 88°
Display Colours	16.7 M
Video Synchronization	TTL Positive or Negative
PC Compatible Frequency	30-80KHz(H) / 50-75Hz(V)
Adjustable Colour Temperature	9300K / 6500K / 5800K / User
Video Compatibility	Multi-Standard for NTSC / PAL
Aspect Ratio	16:9 Ratio With 4:3 Function
VGA Auto Frequency correction	Yes
Speaker	Multimedia Speakers
Number of Speakers	Right x 1, Left x 1, 2.5W
Sound Demodulation	Stereo, Audio
Mute	Yes
Work Humidity	20 % - 80 %
Work Temperature	0-50° C / 32 - 122° F
Volume +/- Power On/Off	Yes



### POWER

Power Supply	Built In
Voltage	AC 110 - 240V 50 / 60Hz
Power Consumption	< 80 W in "ON" Mode

### OSD CONTROLS

Contrast, Brightness, OSD Duration, H-Position, V-Position, Language, Picture Mode, Colour Temp, Scale, Saturation, Backlight, Sleep Timer, Sound, Memory Recall, 3D NR, MPEG NR, PIP, POP Media OSD - Language, Slideshow Duration, slideshow Mode, Music Repeat Mode, Movie Repeat Mode, Display Mode, Autorun, Default, Photo, Music, Movie, Text, File

### OSD LANGUAGE

English, French, German, Spanish, Italian, Russian, Polish and Portuguese

### IN/OUT INTERFACE

Video Interface	HDMI x1 S-Video x 1 VGA x 1 SD Card Reader x 1 Camera Out x 1 BNC x 1 In / BNC x1 Out
Audio Interface	Audio In x 1, Audio L x 1, Audio R x 1
Power Interface	AC In x 1
Termination	75 Ohms (Automatic termination)
Safety & EMC Certification	Energy Star / CE / FCC / ROHS / WEEE
Vesa Standard Mount	200 x 200mm
Stand Type	None
Colour	Black
Button Position	Back, Right
Packing Dimension	TBA
NET Weight	TBA
GROSS Weight	TBA

### ACCESSORIES

Kettle Lead / VGA Cable / Audio Cable / User Manual / Remote Control



