



SMALL LED/LCD

DSM5WGF

5" Active Matrix with Metal Case Glass Fronted

DSM5WGF

| | |
|-------------------------------|---|
| Panel Type | 5" (4:3) LED Monitor with Glass Front |
| Case Type | Metal |
| Maximum Resolution | 640 (H) x 480 (V) |
| Active Display Area | 101.568 x 76.176 (V) mm |
| Pixel Pitch | 0.0529 (H) x 0.1587 (V) mm |
| Bezel Thickness | 24.21 mm |
| Contrast Ratio | 500 : 1 Ratio |
| Brightness | 200 cd/ m ² |
| Response Time | 10ms - 15ms |
| Viewing Angle | U/D: 50° / 70°, L/R: 70° / 70° |
| Display Colours | 16.7 M |
| Video Synchronization | Yes |
| PC Compatible Frequency | 30-80KHz(H) / 50-75Hz(V) Max. 640 x 480 |
| Video Compatibility | Multi-Standard for NTSC / PAL |
| Aspect Ratio | 4 : 3 Ratio |
| VGA Auto Frequency correction | Yes |
| Speaker | No |
| Number of Speakers | No |
| Sound Demodulation | No |
| Mute | No |
| Work Humidity | 20 % - 70 % |
| Work Temperature | - 10 to 50 °C |
| Volume +/- Power On/Off | Yes |



POWER

| | |
|-------------------|------------------------|
| Power Supply | 12VDC, 1amp |
| Voltage | AC100 - 240V 50 / 60Hz |
| Power Consumption | < 12W in "ON" |

IN/OUT INTERFACE

| | |
|----------------------------|--|
| Video Interface | BNC Input x 2 |
| Audio Interface | None |
| Power Interface | DC In x 1 |
| Termination | 75 Ohms (Automatic termination) |
| Safety & EMC Certification | ROHS-2, CE, FCC, C-Tick, E13, WEEE, Energy Star. |
| Vesa Standard Mount | 44 x 24 mm (in base) |
| Stand Type | Multi Functional Desktop/ Wall mount |
| Colour | Black |
| Packing Dimension | 270 (W) x 210 (H) x 120 (D) mm |
| NET Weight | 0.8 Kg |
| GROSS Weight | 1.1 Kg |

OSD CONTROLS

Contrast, Brightness, Language, Colour, Tint, Rotation Up/Down, Input source AV1, AV2, Reset

OSD LANGUAGE

English, French, German, Spanish, Italian, Russian, Polish, Portuguese

ACCESSORIES

Power Supply, Remote Control, Multi Functional Bracket Desktop/ Wall Mount, User Manual.

