



PCT TOUCHSCREEN

DS104PCT

10.4" LED Touchscreen

DS104PCT

Panel Type	10.4" LED Touchscreen
Case Type	Metal
Maximum Resolution	800 x 600
Active Display Area	221.5 (W) x 158.4 (H)
Pixel Pitch	0.264 (W) x 0.264 (H)
Bezel Thickness	40.6 mm
Contrast Ratio	500:1
Brightness	300cd/m ²
Response Time	12ms
Viewing Angle	U/D: 50° / 60°, L/ R: 75° / 75°
Display Colours	16.7m
PC Compatible Frequency	Horizontal Scanning Frequency: 23/24/25/29/30/50/56/59/60 /70/72/75/80/85 Hz Vertical Scanning Frequency:25-77 KHz
Video Compatibility	PAL/NTSC
Aspect Ratio	4:3
VGA Auto Frequency correction	Yes
Work Humidity	90% max.
Work Temperature	-20° to 80°



POWER

Power Supply	12V DC 1Amp
Voltage	AC100 - 240V 50 / 60Hz
Power Consumption	<10W in ON mode

IN/OUT INTERFACE

Video Interface	USB, HDMI, VGA, BNC, DVI
Audio Interface	Yes
Safety & EMC Certification	EN60601 / CE / FCC / ROHS
Vesa Standard Mount	75 x 75mm
Stand Type	Desk
Colour	Black
Button Position	Back, Right
Packing Dimension	360 x 90 x 320mm
NET Weight	2.4Kg
GROSS Weight	2.8Kg

OSD CONTROLS

Colour, Image Setting, OSD Menu, Signal Source, Audio, Exit

OSD LANGUAGE

English, Chinese, German, French, Spanish, Portuguese, Russian, Italian and Polish

PCT Touchscreen

TouchType	Projective Capacitive, Multi Point (10)
Touch Screen Life	Over 30 million touches
Touch Screen Material	Glass
Surface Coating Hardness	3H
Operation Pressure	<10g
Transmittance	>87%
Supported OS	Windows XP, Win7, Win8, Android

ACCESSORIES

Power Cord, Power Adapter, Stand, User Manual, VGA Cable



