

## DS104PCT

10.4" LED Touchscreen

### DS104PCT

Panel Type	10.4" LED Touchscreen
Case Type	Metal
Maximum Resolution	800 x 600
Active Display Area	221.5 (W) x 158.4 (H)
Pixel Pitch	0.264 (W) x 0.264 (H)
Bezel Thickness	40.6 mm
Contrast Ratio	500:1
Brightness	300cd/m <sup>2</sup>
Response Time	12ms
Viewing Angle	U/D: 50° / 60°, L/ R: 75° / 75°
Display Colours	16.7m
PC Compatible Frequency	Horizontal Scanning Frequency: 23/24/25/29/30/50/56/59/60 /70/72/75/80/85 Hz Vertical Scanning Frequency:25-77 KHz
Video Compatibility	PAL/NTSC
Aspect Ratio	4:3
VGA Auto Frequency correction	Yes
Work Humidity	90% max.
Work Temperature	-20° to 80°

### IN/OUT INTERFACE

Video Interface	USB, HDMI, VGA, BNC, DVI
Audio Interface	Yes
Safety & EMC Certification	EN60601 / CE / FCC / ROHS
Vesa Standard Mount	75 x 75mm
Stand Type	Desk
Colour	Black
Button Position	Back, Right
Packing Dimension	360 x 90 x 320mm
NET Weight	2.4Kg
GROSS Weight	2.8Kg

### PCT Touchscreen

TouchType	Projective Capacative, Multi Point (10)
Touch Screen Life	Over 30 million touches
Touch Screen Material	Glass
Surface Coating Hardness	3H
Operation Pressure	<10g
Transmittance	>87%
Supported OS	Windows XP, Win7, Win8, Android



### POWER

Power Supply	12V DC 1Amp
Voltage	AC100 - 240V 50 / 60Hz
Power Consumption	<10W in ON mode

### OSD CONTROLS

Colour, Image Setting, OSD Menu, Signal Source, Audio, Exit

### OSD LANGUAGE

English, Chinese, German, French, Spanish, Portuguese, Russian, Italian and Polish

### ACCESSORIES

Power Cord, Power Adapter, Stand, User Manual, VGA Cable



