



# PCT TOUCHSCREEN

## DS150PCT

15" LED Touchscreen

### DS150PCT

Panel Type	15" LED Touchscreen
Case Type	Metal
Maximum Resolution	1024 x 768
Active Display Area	304.1 (W ) x 228.1 (H)
Pixel Pitch	0.297 (W ) x 0.297 (H)
Bezel Thickness	46 mm
Contrast Ratio	600:1
Brightness	350cd/m <sup>2</sup>
Response Time	5ms
Viewing Angle	U/D: 70° / 70°, L/ R: 80° / 80°
Display Colours	16.7m
PC Compatible Frequency	Horizontal Scanning Frequency: 23/24/25/29/30/50/56/59/60 /70/72/75/80/85 Hz Vertical Scanning Frequency:25-77 KHz
Video Compatibility	PAL/NTSC
Aspect Ratio	4:3
VGA Auto Frequency correction	Yes
Work Humidity	90% max.
Work Temperature	-20° to 80°



### IN/OUT INTERFACE

Video Interface	USB, HDMI, VGA, DVI
Audio Interface	Yes
Safety & EMC Certification	EN60601 / CE / FCC / ROHS
Vesa Standard Mount	100 x 100mm
Stand Type	Desk
Button Position	Back, Right
Packing Dimension	435 x 120 x 350mm
NET Weight	4.2 Kg
GROSS Weight	5.6 Kg

### PCT Touchscreen

TouchType	Projective Capacative, Multi Point (10)
Touch Screen Life	Over 30 million touches
Touch Screen Material	Glass
Surface Coating Hardness	3H
Operation Pressure	<10g
Transmittance	>87%
Supported OS	Windows XP, Win7, Win8, Android

### POWER

Power Supply	12V DC 3Amp
Voltage	AC100 - 240V 50 / 60Hz
Power Consumption	<20W in ON mode

### OSD CONTROLS

Colour, Image Setting, OSD Menu, Signal Source, Audio, Exit

### OSD LANGUAGE

English, Chinese, German, French, Spanish, Portuguese, Russian, Italian and Polish

### ACCESSORIES

Power Cord, Power Adapter, Stand, User Manual, VGA Cable



