



PCT TOUCHSCREEN

DS190PCT

19" LED Touchscreen

DS190PCT

Panel Type	19" LED Touchscreen
Case Type	Metal
Maximum Resolution	1280 x 1024
Active Display Area	376.32 (W) x301.06 (H)
Pixel Pitch	0.294 (W) x0.294 (H)
Bezel Thickness	46 mm
Contrast Ratio	1000:1
Brightness	250cd/m ²
Response Time	5ms
Viewing Angle	U/D: 80° / 80°, L/ R: 85° / 85°
Display Colours	16.7m
PC Compatible Frequency	Horizontal Scanning Frequency: 23/24/25/29/30/50/56/59/60 /70/72/75/80/85 Hz Vertical Scanning Frequency:25-77 KHz
Video Compatibility	PAL/NTSC
Aspect Ratio	4:3
VGA Auto Frequency correction	Yes
Work Humidity	90% max.
Work Temperature	-20° to 80°



POWER

Power Supply	12V DC 3Amp
Voltage	AC100 - 240V 50 / 60Hz
Power Consumption	<25W in ON mode

IN/OUT INTERFACE

Video Interface	USB, HDMI, VGA, DVI
Audio Interface	Yes
Safety & EMC Certification	EN60601 / CE / FCC / ROHS
Vesa Standard Mount	100 x 100mm
Stand Type	Desk
Button Position	Back, Right
Packing Dimension	505 x 173 x 525mm
NET Weight	5.3 Kg
GROSS Weight	7.3 Kg

OSD CONTROLS

Colour, Image Setting, OSD Menu, Signal Source, Audio, Exit

OSD LANGUAGE

English, Chinese, German, French, Spanish, Portuguese, Russian, Italian and Polish

PCT Touchscreen

TouchType	Projective Capacative, Multi Point (10)
Touch Screen Life	Over 30 million touches
Touch Screen Material	Glass
Surface Coating Hardness	3H
Operation Pressure	<10g
Transmittance	>87%
Supported OS	Windows XP, Win7, Win8, Android

ACCESSORIES

Power Cord, Power Adapter, Stand, User Manual, VGA Cable



