



HD-SDI

DS23.6SDI

23.6" (16:9) LED Monitor

DS23.6SDI

Panel Type	23.6" (16:9) LED Monitor Metal Cased
Maximum Resolution	1920(H) x 1080(V)
Active Display Area	521.28 (H) × 293.22 (V) mm
Pixel Pitch	0.2715 (H) x 0.2715 (V) mm
Bezel Thickness	16.7mm
Contrast Ratio	1000:1
Brightness	300 cd/ m ²
Response Time	1.5 - 3.5ms
Viewing Angle	U/D: 80° / 80°, L/R: 85° / 85°
Display Colours	16.7 M
Video Synchronization	Yes
PC Compatible Frequency	30-80KHz(H) / 50-75Hz(V)
Adjustable Colour Temperature	9300K / 6500K / 5800K / User
Video Compatibility	Multi-Standard for NTSC / PAL
Aspect Ratio	16: 9 With 4:3 Function
VGA Auto Frequency correction	Yes
Speaker	Multimedia Speakers
Number of Speakers	Right x 1, Left x 1, 2.5W
Sound Demodulation	Stereo, Audio
Mute	Yes
Work Humidity	20 % - 70 %
Work Temperature	-10 to 50 °C
Volume +/- Power On/Off	Yes



POWER

Power Supply	12VDC, 3amp
Voltage	AC100 - 240V 50 / 60Hz
Power Consumption	<35W in 'ON' mode

IN/OUT INTERFACE

Video Interface	HDMI x1 VGA x 1, BNC x 2 In/ BNC x 2 Out, SDI In / SDI Out
Audio Interface	Audio In x 1
Power Interface	AC In x 1
Termination	75 Ohms (Automatic termination)
Safety & EMC Certification	CE / FCC / ROHS
Vesa Standard Mount	100 x 100mm
Stand Type	Desktop
Colour	Black
Button Position	Front, Right
Packing Dimension	640 (W) x 500 (H) x 165 (D) mm
NET Weight	7.5Kg
GROSS Weight	8.9Kg

OSD CONTROLS

Contrast, Brightness, OSD Duration, H-Position, V-Position, Language, Picture Mode, Colour Temp, Scale, Saturation, Backlight, Sleep Timer, Sound, Memory Recall, 3D NR, MPEG NR, PIP, POP

OSD LANGUAGE

English, French, German, Spanish, Italian, Russian, Polish and Portuguese

ACCESSORIES

Power Supply / Kettle Lead /VGA Cable / Audio Cable / User Manual / Remote Control



