

LED TOUCHSCREEN

DS236PCT

LED Touchscreen with Metal Case

DS236PCT

Panel Type	LED Touchscreen
Case Type	Metal
Maximum Resolution	1920 x 1080
Active Display Area	522.8 (W) x 294.8 (H) mm
Pixel Pitch	0.2715 (W) x 0.2715 (H)
Bezel Thickness	L/R : 10.96mm T/B : 22.31mm
Contrast Ratio	3000 : 1 Ratio
Brightness	250 cd / m ²
Response Time	5m.sec
Viewing Angle	U/D: 80° / 80°, L/ R: 85° / 85° / 170° / 170°
Display Colours	16.7m
Video Synchronisation	Yes - Horizontal Scanning
PC Compatible Frequency	23/24/25/29/30/50/56/59/60 /70/72/75/80/85 Hz Vertical Scanning Frequency: 25 - 77 KHz
Video Compatibility	NTSC / PAL
Aspect Ratio	4 : 3
VGA Auto Frequency Correction	Yes
Work Humidity	90% max.
Work Temperature	-20 to + 80 °C



IN / OUT INTERFACE

Video Interface	USB, HDMI, VGA, DVI
Audio	2 x Input
Certification	EN60601 / CE / FCC / ROHS
Stand Type	Desk
Vesa Standard Mount	200mm x 200mm
Colour	Black
Button Position	Back, Right
Packing Dimensions	655 x 185 x 520mm
Nett Weight	8.6 Kgs
Gross Weight	9.2 Kgs

PCT TOUCHSCREEN

TouchType	Projective Capacitive, Multi Point (10)
Touch Screen Life	Over 30 million touches
Touch Screen Material	Glass
Surface Coating Hardness	7H
Operation Pressure	<10g
Transmittance	>87%
Supported OS	Windows XP, Win7, Win8, Android

POWER

Power Supply	12v DC 3 Amp
Voltage	AC100 - 240V 50 / 60Hz
Power Consumption	35W in "ON"

OSD CONTROLS

Colour, Image Setting, OSD Menu, Signal Source, Audio, Exit

OSD LANGUAGE

English, Chinese, German, French, Spanish, Portuguese, Russian, Italian and Polish

ACCESSORIES

Power Cord, Power Adapter, Stand, User Manual, VGA Cable

