



PUBLIC VIEW/DIGITAL SIGNAGE

DS23.6PVM

LED back light with SD Card reader

DS23.6PVM

Panel Type	23.6" (16:9) LCD Public viewing Monitor Metal Cased
Maximum Resolution	1920(H) x 1080(V)
Active Display Area	521.28 x 293.22 (V) mm
Pixel Pitch	0.2715 (H) x 0.2715 (V) mm
Contrast Ratio	1000:1
Brightness	300 cd/ m ²
Response Time	3.5 ms
Viewing Angle	U/D: 80° / 80°, L/ R: 85° / 85°
Display Colours	16.7 M
Video Synchronization	TTL Positive or Negative
PC Compatible Frequency	30-80KHz(H) / 50-75Hz(V)
Adjustable Colour Temperature	9300K / 6500K / 5800K / User
Video Compatibility	Multi-Standard for NTSC / PAL
Aspect Ratio	16: 9 With 4:3 Function
VGA Auto Frequency correction	Yes
Speaker	Multimedia Speakers
Number of Speakers	Right x 1, Left x 1, 2.5W
Sound Demodulation	Stereo, Audio
Mute	Yes
Work Humidity	20 % - 80 %
Work Temperature	0 - 50° C / 32 - 122° F
Volume +/- Power On/Off	Yes



POWER

Power Supply	24VDC, 2 amp
Voltage	AC100 - 240V 50 / 60Hz
Power Consumption	<35W in ON mode

IN/OUT INTERFACE

Video Interface	HDMI x1 S-Video x 1 VGA x 1 SD Card Reader x 1 Camera Out x 1 BNC x 1 In / BNC x1 Out
Audio Interface	Audio In x 1, Audio L x 1, Audio R x 1
Power Interface	AC In x 1
Termination	75 Ohms (Automatic termination)
Safety & EMC Certification	Energy Star / CE / FCC / ROHS / WEEE
Vesa Standard Mount	100 x 100mm
Stand Type	None
Colour	Black
Button Position	Back, Right
Packing Dimension	65.5 x 18.5 x 52cms
NET Weight	6.9Kg
GROSS Weight	8.9Kg

OSD CONTROLS

Contrast, Brightness, OSD Duration, H-Position, V-Position, Language, Picture Mode, Colour Temp, Scale, Saturation, Backlight, Sleep Timer, Sound, Memory Recall, 3D NR, MPEG NR, PIP, POP Media OSD - Language, Slideshow Duration, slideshow Mode, Music Repeat Mode, Movie Repeat Mode, Display Mode, Autorun, Default, Photo, Music, Movie, Text, File

OSD LANGUAGE

English, French, German, Spanish, Italian, Russian, Polish and Portuguese

ACCESSORIES

Power Supply / Kettle Lead / VGA Cable / Audio Cable / User Manual / Remote Control

