

DSMH21.5LED-WGF

DSMH21.5LED-WGF

Panel Type	21.5" (16:9) LED Monitor with Glass Front
Case Type	Metal
Maximum Resolution	1920 (H) x 1080 (V)
Active Display Area	476.64 (H) x 268.11 (V) mm
Pixel Pitch	0.24825 (H) x 0.24825 (V) mm
Bezel Thickness	Sides: 16mm, Top: 16mm, Bottom: 29mm
Contrast Ratio	1000 : 1
Brightness	250 cd/m ²
Response Time	1.5 - 3.5ms
Viewing Angle	U/D: 80° / 80°, L/R: 85° / 85°
Display Colours	16.7 M
Video Synchronization	Yes
PC Compatible Frequency	30-80KHz(H) / 50-75Hz(V)
Adjustable Colour Temperature	9300K / 6500K / 5800K / User
Video Compatibility	Multi-Standard for NTSC / PAL
Aspect Ratio	16:9
VGA Auto Frequency correction	Yes
Number of Speakers	Right x 1 Left x 1. 2.5W
Sound Demodulation	Stereo. Audio
Mute	Yes
Work Humidity	20 % - 70 %
Work Temperature	-10 to 50 °C
Volume +/- Power On/Off	Yes

IN/OUT INTERFACE

Video Interface	HDMI x1, VGA x 1, BNC x 2 In/ BNC x 2 Out
Audio Interface	Audio In x 1, Audio L x 1, Audio R x 1
Power Interface	DC In x 1
Termination	75 Ohms (Automatic termination)
Safety & EMC Certification	CE / FCC / ROHS / WEEE
Vesa Standard Mount	100 x 100mm
Stand Type	Picture Frame
Colour	Black
Packing Dimension	610 (W) x 510 (H) x 170 (D) mm
NET Weight	5.5 Kg
GROSS Weight	7.1 Kg



POWER

Power Supply	12VDC, 3amp
Voltage	AC100 - 240V 50 / 60Hz
Power Consumption	<30W in ON mode

OSD CONTROLS

Contrast, Brightness, OSD Duration, H-Position, V-Position, Language, Picture Mode, Colour Temp, Scale, Saturation, Backlight, Sleep Timer, Sound, Memory Recall, 3D NR, MPEG NR, PIP, POP

OSD LANGUAGE

English, French, German, Spanish, Italian, Russian, Polish and Portuguese

ACCESSORIES

Power Supply / Kettle Lead
HDMI Cable / User Manual / Remote Control

