

LED CCTV MONITOR

AS19LED-2.

LED Monitor with Plastic Case

AS19LED-2.

Panel Type	19" LED
Case Type	Plastic
Maximum Resolution	1280 x 1024
Active Display Area	376.32 (H) x 301.056 (V) mm
Pixel Pitch	0.294 (H) x 0.294 (V) mm
Bezel Thickness	L / R / U / D: 23.55 mm
Contrast Ratio	1000 : 1 Ratio
Brightness	300 cd / m ²
Response Time	5m.sec
Viewing Angle	170 / 160
Display Colours	16.7m
Video Synchronisation	Yes
PC Compatibility	30-60 KHz (H) / 56-75Hz (V)
Aspect Ratio	4 : 3
VGA Auto Frequency Correction	Yes
Speakers	2 W
Number of Speakers	2
Sound Demodulation	Stereo. Audio
Mute	Yes
Work Humidity	5% - 90%
Work Temperature	-10 to +50 °C
Volume +/- Power On/Off	Yes

IN / OUT INTERFACE

Video Interface	BNC (CVBS) in x 1, BNC (CVBS) out, HDMI in x 1, VGA in x 1
Audio	PC Audio in
Power Interface	DC12V in x 1
Termination	75 ohm
Certification	CE, FCC, ROHS
VESA	75 x 75
Stand Type	Desk
Colour	Black
Button Position	Right Bottom, front of case
Packing Dimensions	500 x 440 x 470 mm
Nett Weight	3.1 Kgs
Gross Weight	4.15 Kgs



POWER

Power Supply	12v DC 3 Amp
Voltage	110 / 240v AC
Power Consumption	25watt (Max)

OSD CONTROLS

Contrast, Brightness, Colour Temperature, Sharpness, Prevent-Picture-Burn-In, Sound volume, OSD position, OSD transparency, Background colour, Factory reset

OSD LANGUAGE

English, German, Spanish, French, Italian, Polish, Danish and Dutch

ACCESSORIES

HDMI cable, PSU, Remote control, User Manual

