

4K UHD LED

PD434-4KLED

4K UHD LED Monitor With Screen Splitting Function

PD434-4KLED

Panel Type	43" (16:9) 4K LED Backlit Monitor
Case Type	Metal
Maximum Resolution	3840 x 2160 @ 60Hz
Active Display Area	941.18 (H) x 529.41 (V)
Pixel Pitch	0.2451 (H) x 0.2451 (V)
Bezel Thickness	L/R/U: 14.4mm, D:27mm
Contrast Ratio	3000 : 1
Brightness	350 cd / m ²
Response Time	5m.sec (G to G)
Viewing Angle	178 / 178 °
Display Colours	1.073B
Display Mode	Quad, Pip, Pop
Video Synchronisation	Yes
PC Compatibility	Yes
Aspect Ratio	16 : 9
VGA Auto Frequency Correction	Yes
Speakers	5W x 2
Number of Speakers	2
Sound Demodulation	Stereo. Audio
Mute	Yes
Work Humidity	5% - 90%
Work Temperature	-10 to +50 °C
Volume +/- Power On/Off	Yes

IN / OUT INTERFACE

Video Interface	1 x HDMI v2.0 input, 3 x HDMI v1.4 input. 1 x DP v1.2 input
Audio	PC audio out
Power Interface	AC in
Termination	75 ohm
Certification	CE, FCC, ROHS
VESA	200 x 200
Stand Type	Desk
Colour	Black
Button Position	Bottom right
Packing Dimensions	1005 x 610 x 160mm
Nett Weight	17.6 Kgs
Gross Weight	20 Kgs



POWER

Power Supply	N/a
Voltage	110 / 230v AC
Power Consumption	85 watt(typical)

OSD CONTROLS

Region Adjust for PIP & PBP:1P, 2P LR, 2P TB, 2P PIP, 4P, SET, Contrast, Ultra Vivid, Gamma, Colour Temperature, Collor Effect, Saturation, Hue, Current Mode, Input, Audio Input, Display Function, Select Region, OSD language, OD (over drive), Auto selection, Reset.

OSD LANGUAGE

English, German, French, Spanish and Portuguese

ACCESSORIES

Remote, power cable, HDMI cable, User's manual

