

LED MONITOR

DS156FHD

LED Monitor

DS156FHD

| | |
|-------------------------------|----------------------------------|
| Panel Type | 15.6" (16:9) LED Monitor |
| Case Type | Metal |
| Maximum Resolution | 1920 (H) x 1080 (V) |
| MTBF | 40,000 hrs |
| Active Display Area | 344.16 (H) x 193.59 (V) mm |
| Pixel Pitch | 179.25 (H) x 179.25 (V)mm |
| Bezel Thickness | T: 15.4mm L/R: 19.7mm, B: 38.1mm |
| Contrast Ratio | 800 : 1 |
| Brightness | 250 cd / m ² |
| Response Time | 10+15m.sec (G to G) |
| Viewing Angle | 85 / 85 U / D 85 / 85° |
| Display Colours | 16.7 M |
| PC Compatibility | Yes |
| Aspect Ratio | 16:9 |
| VGA Auto Frequency Correction | Yes |
| Speakers | 2 |
| Mute | Yes |
| Work Humidity | 0% - 80% |
| Work Temperature | 0 - +50 °C |
| Volume +/- Power On/Off | Yes |

IN / OUT INTERFACE

| | |
|--------------------|---|
| Video Interface | VGA, HDMI, 1 x BNC in, 1 x BNC out, Audio |
| Audio | 3.5mm |
| Termination | 75 ohm |
| Certification | FCC ,CE, ROHS-2 |
| VESA | 100 x 100 |
| Stand Type | Picture Frame |
| Colour | Black |
| Button Position | Front |
| Packing Dimensions | 410mm x 410mm x 150mm |
| Nett Weight | 3.3 Kgs |
| Gross Weight | 4.0 Kgs |



POWER

| | |
|-------------------|-----------|
| Power Supply | 12v 2 Amp |
| Power Consumption | 15 Watt |
| Power Interface | DC 2.1mm |

OSD CONTROLS

VIDEO-Picture, Brightness, Contrast, Color, Sharpness, Colour Temp, Advance Control, Focus, AUDIO-Sound Mode, Balance, Bass, Treble, Virtual Surround, AVL, Camera, SETTING-Menu Language, Picture Format, Menu Timeout, Menu Transparency, Power On status, Blue Screen System Reset

OSD LANGUAGE

English, French, German, Spanish, Italian, Russian, Portuguese, Polish, Arabic & Korean

ACCESSORIES

Power supply, Stand, Remote Control, User Guide, HDMI Cable

