

# LED MONITOR

## AS19LED-3

### LED Monitor

#### AS19LED-3

Panel Type	LED
Case Type	Plastic
Maximum Resolution	1280 (H) x 1024 (V)
MTBF	50,000 hrs
Active Display Area	376.32 x 301.056 (HxV)
Pixel Pitch	0.294 x 0.294 (HxV) mm
Bezel Thickness	Left/Right 20mm, Top 20mm, Bottom 35mm
Contrast Ratio	1000 : 1
Brightness	250 cd / m <sup>2</sup>
Response Time	5m.sec (G to G)
Viewing Angle	170 / 160° (H/V)
Display Colours	16.7 M
Video Synchronisation	Yes
PC Compatibility	Yes
Aspect Ratio	4:3
VGA Auto Frequency Correction	Yes
Speakers	2
Sound Demodulation	Yes
Mute	Yes
Work Humidity	5% - 90%
Work Temperature	-10 - +50 °C
Volume +/- Power On/Off	Yes

#### IN / OUT INTERFACE

Video Interface	1 x BNC composite in, 1 x BNC composite out, 1 x VGA, 1 x HDMI
Audio	1 x Input
Termination	75 ohm
Certification	CE, FCC, ROHS
VESA	75 x 75 cm
Stand Type	Table stand
Colour	Black
Button Position	Back side bottom
Packing Dimensions	510mm x 175mm x 525mm
Gross Weight	6.1kgs



#### POWER

Power Supply	12v DC 3 Amp
Power Consumption	25 Watt
Voltage:	110 - 240v AC
	50 - 60Hz
Power Interface	DC 2.1mm

#### OSD CONTROLS

Contrast, Brightness, Colour, Sharpness,  
Colour temperature

#### OSD LANGUAGE

English, German, Italian, Spanish, French,  
Russian, Portugese, Polish

#### ACCESSORIES

DC adaptor, Power cable, HDMI cable,  
User Manual

