

# LED MONITOR

## DS236AHDA-2

### LED Monitor

#### DS236AHDA-2

Panel Type	23.6" Led Monitor
Case Type	Plastic
Maximum Resolution	1920 (H) x 1080 (V)
MTBF	50,000 hrs
Active Display Area	521.28 x 293.22 (HxV)
Pixel Pitch	0.2715 x 0.2715 (HxV) mm
Bezel Thickness	Left / Right / Top 2mm, Bottom 16mm
Contrast Ratio	1000 : 1
Brightness	250 cd / m <sup>2</sup>
Response Time	5m.sec (G to G)
Viewing Angle	178 / 178° (H/V)
Display Colours	16.7m
Video Synchronisation	Yes
PC Compatibility	N/A
Aspect Ratio	16:9
VGA Auto Frequency Correction	N/A
Speakers	0
Sound Demodulation	No
Mute	N/A
Work Humidity	5% - 90%
Work Temperature	0 - 40 °C
Volume +/- Power On/Off	Yes



#### IN / OUT INTERFACE

Video Interface	2 x HD analogue BNC in (CVBS, AHD, CVI, TVI) 2 x HD analogue BNC out (CVBS, AHD, CVI, TVI) HDMI in
Audio Interface	No
Termination	75 Ohms
Certification	FCC-DOC, CE, ROHS
VESA	100mm x 100mm
Stand Type	Desk
Colour	Black
Button Position	Front, Bottom Right
Packing Dimensions	598mm x 110mm x 400mm
Gross Weight	5.8kg

#### POWER

Power Supply	220 / 240 AC
Power Consumption	30 Watt
Voltage:	12v DC
Power Interface	DC in x 1

#### OSD CONTROLS

Contrast, Brightness, Saturation, Hue,  
Language, OSD position, OSD Time, Reset

#### OSD LANGUAGE

English, French, German, Spanish, Italian,  
Dutch, Polish, Russian, Danish

#### ACCESSORIES

Power Cord, Adapter, Stand, Users Guide,  
HDMI Cable

