

# 50" LED MONITOR

DSM50-4KLED

50" LED Monitor

## DSM50-4KLED

Panel Type	LED
Case Type	Metal
Maximum Resolution	3840 (H) x 2160 (V)
MTBF	50,000 hrs
Active Display Area	1095.84 × 616.41 (H×V)
Pixel Pitch	0.2865x 0.2865mm
Bezel Thickness	Left / Right / Top 12mm, Bottom 15mm
Contrast Ratio	4000 : 1
Brightness	400 cd / m <sup>2</sup>
Response Time	9.5m.sec (G to G)
Viewing Angle	178 / 178° (H/V)
Display Colours	1.07B (10-bit)
Video Synchronisation	Yes
PC Compatibility	Yes
Aspect Ratio	16:9 / 4:3
VGA Auto Frequency Correction	N/A
Speakers	0
Sound Demodulation	N/A
Mute	N/A
Work Humidity	5% - 90%
Work Temperature	0 - 40 °C
Volume +/- Power On/Off	Yes

## IN / OUT INTERFACE

Video Interface	1 x HDMI v2.0 input, 2 x HDMI v1.4 input, 1 x DP v1.2 input
Audio	1 x Output
Termination	N/A
Certification	CE, FCC, ROHS
VESA	200 x 400
Stand Type	Desk stand
Colour	Black
Button Position	Back bottom right
Packing Dimensions	1270mm x 250mm x 850mm



## POWER

Power Supply	N/A
Power Consumption	<110W
Voltage:	AC110~240V
Power Interface	AC110~240V

## OSD CONTROLS

Contrast, Brightness, DCR, Saturation, OSD position, Gamma, Color temp, Hue, Low blue light, Sharpness, Noise reduction, Aspect Ratio, Mute, Volume, Multi-Window, OSD position

## OSD LANGUAGE

English, French, Russian, Spanish, German, Italian, Portuguese, Turkish, Danish, Polish and Dutch

## ACCESSORIES

Power cord, Stand, User's guide, HDMI cable, Remote control

